SAFETY DATA SHEET



Date of issue/Date of revision 29 May 2021 Version 2.03

Section 1. Identification		
Product name	: STEEL WOOL ALL GRADES	
Product code	: 00384715	
Other means of identification	: Not available.	
Product type	: Solid.	
Relevant identified uses of the substance or mixture and uses advised against		
Product use	: Consumer applications, Professional applications.	
Use of the substance/ mixture	: Polish	
Uses advised against	: Not applicable.	
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
<u>Emergency telephone</u> <u>number</u>	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)	
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)	

Section 2. Hazards identification

Precautionary statements Prevention Response	: Not applicable. : Not applicable.
Hazard statements	: No known significant effects or critical hazards.
Signal word	: No signal word.
GHS label elements	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 98.5% (dermal), 98.5% (inhalation)
Classification of the substance or mixture	for employees and other users of this product. Not classified.
OSHA/HCS status	While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available

Product name STEEL WOOL ALL GRADES

Section 2. Hazards identification

Disposal	: Not applicable.
Supplemental label elements	: Sanding and grinding dusts may be harmful if inhaled. Emits toxic fumes when heated.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: STEEL WOOL ALL GRADES

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person. Description of necessary first aid measures

Eye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids
apart for at least 10 minutes and seek immediate medical advice.Inhalation: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is
irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained
personnel.Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water
or use recognized skin cleanser. Do NOT use solvents or thinners.Ingestion: If swallowed, seek medical advice immediately and show this container or label. Keep
person warm and at rest. Do NOT induce vomiting.

Most important sy	/mptoms/effects.	acute and delayed	

No known significant effects or critical hazards.
No known significant effects or critical hazards.
No known significant effects or critical hazards.
No known significant effects or critical hazards.
<u>ns</u>
No specific data.

Product name STEEL WOOL ALL GRADES

Section 4. First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: No specific fire or explosion hazard.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

United States

Page: 4/10

Product name STEEL WOOL ALL GRADES

Section 7. Handling and storage

Precautions for safe handling	
Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters	
Occupational exposure limi	<u>b</u>
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	
Hygiene measures	 Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Safety glasses with side shields.
Skin protection	
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Product name STEEL WOOL ALL GRADES

Section 8. Exposure controls/personal protection

Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

Section 9. Physical and chemical properties

Physical state:Solid.Color:Not available.Odor:Characteristic.Odor threshold:Not available.pH:Not available.Boiling point:Not available.Boiling point:Not available.Boiling point:Not available.Flash point:Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Vapor density:Solid.aplicable.Relative density:::Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water::::Viscosity:: <t< th=""><th>Appearance</th><th></th></t<>	Appearance																																																																			
Odor:Characteristic.Odor threshold:Not available.pH:Not available.Boiling point:Not available.Boiling point:Not available.Flash point:Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Clower and upper explosive (flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:To<Density (lbs / gal):63.43Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not applicable.Viscosity::Kinematic (40°C (104°F)): Not applicable.Volatility:::Volatility::Volatility::Volatility::Volatility::Volatility::Volatility::Volatility::Volatility::Volatility::Volatility::Volatility::Volatility::Volatility:: <tr <="" th=""><th>Physical state</th><th>: Solid.</th></tr> <tr><th>Odor threshold:Not available.pH:Not available.Boiling point:Not available.Boiling point:Not available.Flash point:Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Cower and upper explosive:Not available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:?Relative density:7.6Density (Ibs / gal):63.43Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not applicable.Viscosity:Kinematic (40°C (104°F)): Not applicable.Volatility::0% (v/v), 0% (w/w)</th><th>Color</th><th>: Not available.</th></tr> <tr><th>pH:Not applicable.Melting point:Not available.Boiling point:Not available.Flash point:Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature:Mot applicable.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Cower and upper explosive:Not available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:63.43Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Kinematic (40°C (104°F)): Not applicable.Viscosity::Kinematic (40°C (104°F)): Not applicable.Volatility:::Volatility::Solubility::Viscosity::Viscosity::Viscosity::Volatility::::::::::::::::::::::::::::::::::::<th>Odor</th><th>: Characteristic.</th></th></tr> <tr><th>Melting point: Not available.Boiling point: Not available.Flash point: Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature: Mot applicable.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Mot available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Mot applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Kinematic (40°C (104°F)): Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.</th><th>Odor threshold</th><th>: Not available.</th></tr> <tr><th>Boiling point:Not available.Boiling point:Not available.Flash point:Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature:Mot available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Mot available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Tot applicable.Relative density:7.6Density (lbs / gal):63.43Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Mot applicable.Viscosity:Kinematic (40°C (104°F)): Not applicable.Volatility::0% (v/v), 0% (w/w)</th><th>рН</th><th>: Not applicable.</th></tr> <tr><th>Flash point: Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature: Mot applicable.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Mot applicable.(flammable) limits: Mot available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Mot applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Kinematic (40°C (104°F)): Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.</th><th>Melting point</th><th>: Not available.</th></tr> <tr><th>Auto-ignition temperature:Not applicable.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Not available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:7.6Density (lbs / gal):63.43Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Kinematic (40°C (104°F)): Not applicable.Volatility::0% (v/v), 0% (w/w)</th><th>Boiling point</th><th>: Not available.</th></tr> <tr><th>Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Not applicable.(flammable) limits: Not available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)</th><th>Flash point</th><th>: Closed cup: 250°C (482°F) [Product does not sustain combustion.]</th></tr> <tr><th>Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Mot applicable.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Mot applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)</th><th>Auto-ignition temperature</th><th>: Not applicable.</th></tr> <tr><th>Lower and upper explosive (flammable) limits: Mot applicable.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)</th><th>Decomposition temperature</th><th>: Not available.</th></tr> <tr><th>(flammable) limitsEvaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Wot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)</th><th>Flammability (solid, gas)</th><th>: Not available.</th></tr> <tr><th>Vapor pressure: Not available.Vapor density: Mot applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)</th><th></th><th>: Not applicable.</th></tr> <tr><th>Vapor density: Not applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)</th><th>Evaporation rate</th><th>: Not available.</th></tr> <tr><th>Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)</th><th>Vapor pressure</th><th>: Not available.</th></tr> <tr><th>Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)</th><th>Vapor density</th><th>: Not applicable.</th></tr> <tr><th>Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)</th><th>Relative density</th><th>: 7.6</th></tr> <tr><th>Partition coefficient: n- octanol/water : Not applicable. Viscosity : Kinematic (40°C (104°F)): Not applicable. Volatility : 0% (v/v), 0% (w/w)</th><th>Density(lbs / gal)</th><th>: 63.43</th></tr> <tr><th>octanol/waterViscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)</th><th>Solubility</th><th></th></tr> <tr><th>Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)</th><th></th><th>: Not applicable.</th></tr> <tr><th>Volatility : 0% (v/v), 0% (w/w)</th><th></th><th></th></tr> <tr><th></th><th>· · · · · · · · · · · · · · · · · · ·</th><th></th></tr> <tr><th>% Solid. (w/w) : 100</th><th>· · · · · · · · · · · · · · · · · · ·</th><th></th></tr> <tr><th></th><th>% Solid. (w/w)</th><th>: 100</th></tr>	Physical state	: Solid.	Odor threshold:Not available.pH:Not available.Boiling point:Not available.Boiling point:Not available.Flash point:Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Cower and upper explosive:Not available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:?Relative density:7.6Density (Ibs / gal):63.43Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not applicable.Viscosity:Kinematic (40°C (104°F)): Not applicable.Volatility::0% (v/v), 0% (w/w)	Color	: Not available.	pH:Not applicable.Melting point:Not available.Boiling point:Not available.Flash point:Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature:Mot applicable.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Cower and upper explosive:Not available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:63.43Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Kinematic (40°C (104°F)): Not applicable.Viscosity::Kinematic (40°C (104°F)): Not applicable.Volatility:::Volatility::Solubility::Viscosity::Viscosity::Viscosity::Volatility:::::::::::::::::::::::::::::::::::: <th>Odor</th> <th>: Characteristic.</th>	Odor	: Characteristic.	Melting point: Not available.Boiling point: Not available.Flash point: Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature: Mot applicable.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Mot available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Mot applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Kinematic (40°C (104°F)): Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.	Odor threshold	: Not available.	Boiling point:Not available.Boiling point:Not available.Flash point:Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature:Mot available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Mot available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Tot applicable.Relative density:7.6Density (lbs / gal):63.43Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Mot applicable.Viscosity:Kinematic (40°C (104°F)): Not applicable.Volatility::0% (v/v), 0% (w/w)	рН	: Not applicable.	Flash point: Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature: Mot applicable.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Mot applicable.(flammable) limits: Mot available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Mot applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Kinematic (40°C (104°F)): Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.	Melting point	: Not available.	Auto-ignition temperature:Not applicable.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Not available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:7.6Density (lbs / gal):63.43Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Kinematic (40°C (104°F)): Not applicable.Volatility::0% (v/v), 0% (w/w)	Boiling point	: Not available.	Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Not applicable.(flammable) limits: Not available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Flash point	: Closed cup: 250°C (482°F) [Product does not sustain combustion.]	Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Mot applicable.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Mot applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Auto-ignition temperature	: Not applicable.	Lower and upper explosive (flammable) limits: Mot applicable.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Decomposition temperature	: Not available.	(flammable) limitsEvaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Wot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Flammability (solid, gas)	: Not available.	Vapor pressure: Not available.Vapor density: Mot applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)		: Not applicable.	Vapor density: Not applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Evaporation rate	: Not available.	Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Vapor pressure	: Not available.	Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Vapor density	: Not applicable.	Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Relative density	: 7.6	Partition coefficient: n- octanol/water : Not applicable. Viscosity : Kinematic (40°C (104°F)): Not applicable. Volatility : 0% (v/v), 0% (w/w)	Density(lbs / gal)	: 63.43	octanol/waterViscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Solubility		Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)		: Not applicable.	Volatility : 0% (v/v), 0% (w/w)				· · · · · · · · · · · · · · · · · · ·		% Solid. (w/w) : 100	· · · · · · · · · · · · · · · · · · ·			% Solid. (w/w)	: 100
Physical state	: Solid.																																																																			
Odor threshold:Not available.pH:Not available.Boiling point:Not available.Boiling point:Not available.Flash point:Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Cower and upper explosive:Not available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:?Relative density:7.6Density (Ibs / gal):63.43Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not applicable.Viscosity:Kinematic (40°C (104°F)): Not applicable.Volatility::0% (v/v), 0% (w/w)	Color	: Not available.																																																																		
pH:Not applicable.Melting point:Not available.Boiling point:Not available.Flash point:Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature:Mot applicable.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Cower and upper explosive:Not available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:63.43Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Kinematic (40°C (104°F)): Not applicable.Viscosity::Kinematic (40°C (104°F)): Not applicable.Volatility:::Volatility::Solubility::Viscosity::Viscosity::Viscosity::Volatility:::::::::::::::::::::::::::::::::::: <th>Odor</th> <th>: Characteristic.</th>	Odor	: Characteristic.																																																																		
Melting point: Not available.Boiling point: Not available.Flash point: Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature: Mot applicable.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Mot available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Mot applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Kinematic (40°C (104°F)): Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.	Odor threshold	: Not available.																																																																		
Boiling point:Not available.Boiling point:Not available.Flash point:Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature:Mot available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Mot available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Tot applicable.Relative density:7.6Density (lbs / gal):63.43Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Mot applicable.Viscosity:Kinematic (40°C (104°F)): Not applicable.Volatility::0% (v/v), 0% (w/w)	рН	: Not applicable.																																																																		
Flash point: Closed cup: 250°C (482°F) [Product does not sustain combustion.]Auto-ignition temperature: Mot applicable.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Mot applicable.(flammable) limits: Mot available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Mot applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Kinematic (40°C (104°F)): Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.	Melting point	: Not available.																																																																		
Auto-ignition temperature:Not applicable.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Not available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:7.6Density (lbs / gal):63.43Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Kinematic (40°C (104°F)): Not applicable.Volatility::0% (v/v), 0% (w/w)	Boiling point	: Not available.																																																																		
Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Not applicable.(flammable) limits: Not available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Flash point	: Closed cup: 250°C (482°F) [Product does not sustain combustion.]																																																																		
Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Mot applicable.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Mot applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Auto-ignition temperature	: Not applicable.																																																																		
Lower and upper explosive (flammable) limits: Mot applicable.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Decomposition temperature	: Not available.																																																																		
(flammable) limitsEvaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Wot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Flammability (solid, gas)	: Not available.																																																																		
Vapor pressure: Not available.Vapor density: Mot applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)		: Not applicable.																																																																		
Vapor density: Not applicable.Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Evaporation rate	: Not available.																																																																		
Relative density: 7.6Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Vapor pressure	: Not available.																																																																		
Density (lbs / gal): 63.43Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Mot applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Vapor density	: Not applicable.																																																																		
Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Relative density	: 7.6																																																																		
Partition coefficient: n- octanol/water : Not applicable. Viscosity : Kinematic (40°C (104°F)): Not applicable. Volatility : 0% (v/v), 0% (w/w)	Density(lbs / gal)	: 63.43																																																																		
octanol/waterViscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)	Solubility																																																																			
Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 0% (v/v), 0% (w/w)		: Not applicable.																																																																		
Volatility : 0% (v/v), 0% (w/w)																																																																				
	· · · · · · · · · · · · · · · · · · ·																																																																			
% Solid. (w/w) : 100	· · · · · · · · · · · · · · · · · · ·																																																																			
	% Solid. (w/w)	: 100																																																																		

Product name STEEL WOOL ALL GRADES

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity			
Conclusion/Summary	: There are no data available on the mixture itself.		
Irritation/Corrosion			
Conclusion/Summary			
Skin	: There are no data available on the mixture itself.		
Eyes	: There are no data available on the mixture itself.		
Respiratory	: There are no data available on the mixture itself.		
Sensitization			
Conclusion/Summary			
Skin	: There are no data available on the mixture itself.		
Respiratory	: There are no data available on the mixture itself.		
Mutagenicity			
Conclusion/Summary	: There are no data available on the mixture itself.		
Carcinogenicity			
Conclusion/Summary	: There are no data available on the mixture itself.		
Reproductive toxicity			
Conclusion/Summary	: There are no data available on the mixture itself.		
Teratogenicity			
Conclusion/Summary	: There are no data available on the mixture itself.		
<u>Specific target organ toxicity (single exposure)</u>			
Not available.			
Specific target organ toxicity (repeated exposure)			

Not available.

Product name STEEL WOOL ALL GRADES

Section 11. Toxicological information

Aspiration hazard

Not available.

Information on the likely routes of exposure

·····,			
Potential acute health effect	its		
Eye contact	: No known significant effects or critical hazards.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		
Over-exposure signs/symptoms			
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: No specific data.		
Ingestion	: No specific data.		
Delayed and immediate effect	cts and also chronic effects from short and long term exposure		
Conclusion/Summary	: There are no data available on the mixture itself. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.		
<u>Short term exposure</u>			
Potential immediate effects	: There are no data available on the mixture itself.		
Potential delayed effects	: There are no data available on the mixture itself.		
Long term exposure			
Potential immediate effects	: There are no data available on the mixture itself.		
Potential delayed effects	: There are no data available on the mixture itself.		
Potential chronic health effects			
General	: No known significant effects or critical hazards.		
Carcinogenicity	: No known significant effects or critical hazards.		
Mutagenicity	: No known significant effects or critical hazards.		
Reproductive toxicity	: No known significant effects or critical hazards.		

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product name STEEL WOOL ALL GRADES

Section 12. Ecological information

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information				
	DOT	IMDG	ΙΑΤΑ	
UN number	UN3077	Not regulated.	Not regulated.	
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (red phosphorus)	-	-	
Transport hazard class (es)	9	-	-	
Packing group	III	-	-	
Environmental hazards	No.	No.	No.	
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	
Product RQ (lbs)	1250	Not applicable.	Not applicable.	
RQ substances	(red phosphorus)	Not applicable.	Not applicable.	

14. Transport information

Additional information

DOT

: The classification of the product is due solely to the presence of one or more US DOT-listed 'Hazardous substances' that are subject to reportable quantity requirements and only applies to shipments of packages greater than, or equal to, the product reportable quantity. Package sizes less than the product reportable quantity are not regulated as hazardous materials.

United States Page: 8/10

Date of issue 29 May 2021

Listed

Product name STEEL WOOL ALL GRADES

14. Transport information

IMDG : None identified.

IATA : None identified.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are active or exempted.

United States - TSCA 5(e) - Substances consent order: Farbon
SARA 302/304
SARA 304 RQ : Not applicable.
Composition/information on ingredients
No products were found.
SARA 311/312
Classification : Not applicable.
Composition/information on ingredients
No products were found.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 1 * Flammability : 1 Physical hazards : 1 (*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)								
Health	:	1	Flammability	1	1	Instability	:	1
Date of previous issue : 10/6/2020								

Product name STEEL WOOL ALL GRADES

Section 16. Other information

Organization that prepared the SDS	: EHS
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.